













COMPATIBILITY

MULTIPLE OPTIONS | WELLER POWER UNITS AND ACCESSORIES

SOLDERING STATIONS

	WD1	WD2	WD1M	WD2M	TIP STYLE
 WSP80	■	■	■	■	LT SERIES
 WP80	■	■	■	■	LT SERIES
 WMP	■	■	■	■	NT SERIES
 WMRP			■	■	RT SERIES
 WMRT			■	■	RTW SERIES
 WTA50	■	■	■	■	WTA SERIES
 WSP150		■		■	LHT SERIES
 WHP80	■	■	■	■	
 WSB80	■	■	■	■	
 WSB150		■		■	
 FE75	■	■	■	■	LT SERIES
 WP120			■	■	XT SERIES



Weller



Electronix Express / RSR Electronics
 365 Blair Road, Avenel, NJ 07001
 Tel. 732-381-8777 or 732-381-802
 FAX 732-381-1006 or 732-381-1572

www.cooperhandtools.com/weller

PRODUCT LINE

FOUR CONFIGURATIONS TO GIVE YOU THE MOST EFFICIENT SOLUTION



USED WITH:
WD1001
WD1002
WD1002T

WD1 SINGLE CHANNEL POWER UNIT

Specifications:
 Voltage 120 V (input); 24 V (output)
 Footprint 5.27" x 4.25" x 5.77" (134 x 108 x 147 mm)
 Power consumption 85W
 Temperature range 150° F - 850° F (50° C - 450° C)
 ESD safe Yes
 Temperature accuracy ± 9° F (± 5° C)
 Temperature stability ± 10° F (± 6° C)



WD2 DUAL CHANNEL POWER UNIT

Specifications:
 Voltage 120 V (input); 24 V (output)
 Footprint 5.27" x 4.25" x 5.77" (134 x 108 x 147 mm)
 Power consumption 160W
 Temperature range 150° F - 850° F (50° C - 450° C)
 ESD safe Yes
 Temperature accuracy ± 9° F (± 5° C)
 Temperature stability ± 10° F (± 6° C)



WD1000M WD1M SINGLE CHANNEL POWER UNIT WITH WMRP MICRO SOLDERING PENCIL AND WMRH SOLDERING PENCIL STAND

Specifications:
 Voltage 120 V (input); 24 V (output)
 Footprint 5.27" x 4.25" x 5.77" (134 x 108 x 147 mm)
 Power consumption 85W
 Temperature range 150° F - 850° F (50° C - 450° C)
 ESD safe Yes
 Temperature accuracy ± 17° F (± 9° C)
 Temperature stability ± 9° F (± 5° C)
 Stand WMRH (Order No. 0051514599)
 Pencil WMRP (Order No. 0052917199)



WD2000M WD2M DUAL CHANNEL POWER UNIT WITH WMRP MICRO SOLDERING PENCIL AND WMRH SOLDERING PENCIL STAND, PLUS WMRT MICRO THERMAL TWEezer AND WMRTH STAND

Specifications:
 Voltage 120 V (input); 24 V (output)
 Footprint 5.27" x 4.25" x 5.77" (134 x 108 x 147 mm)
 Power consumption 160W
 Temperature range 150° F - 850° F (50° C - 450° C)
 ESD safe Yes
 Temperature accuracy ± 17° F (± 9° C)
 Temperature stability ± 9° F (± 5° C)
 Stands WMRH (Order No. 0051514599)
 WMRTH (Order No. 0051514699)
 Pencils WMRP Micro Soldering Pencil (Order No. 0052917199)
 WMRT Micro Tweezers (Order No. 0051317399)

COOPER Hand Tools

Campbell® CaulkMaster® Crescent® Diamond® Erem® Kahnetics® Lufkin®
 Nicholson® Plumb® H.K.Porter® Weller® Wire-Wrap® Wiss® Xcelite®
 CHT08-11635/KINKO/PRINTED 06/08/USA COOPER NO. 550725 © 2008, Cooper Industries, LLC
 Specifications subject to change without notice.

Electronix Express / RSR Electronics
 365 Blair Road, Avenel, NJ 07001
 Tel. 732-381-8777 or 732-381-802
 FAX 732-381-1006 or 732-381-1572